Evidence of Performance

Mortise lock according to EN 12209:2016

Test Report Nr. 24-002165-PR01

(PB-G01-03-en-01)

Client Krona Koblenz S.p.A.

> Via O. Romero 1 47853 Coriano (RN)

Italy

Product Mechanically operated mortise locks

Designation Magnetic lock (code KM 001 CM A)

Performance-relevant

product details

Backset: Distance:

90 mm 8 mm Square spindle:

196 mm x 18 mm x 3,0 mm Faceplate:

50 mm

Lever tumbler hole Holes:

Accessories Strike plate (without classification)

Maintenance As per service manual of the hardware manufacturer

Installation As per installation instructions of the hardware manufacturer

Special features -/-

Classification according to EN 12209:2016

Category of use	Durability	Door mass and closing force	Suitability for use on fire / smoke control doorset	Safety	Corrosion resistance and temperature	Security and drill resistance	Key identification of lever locks
3	С	7	0	0	D	0	0

ift Rosenheim 15.10.2024

GERMANY

Konrad Querengässer, Dipl.-Ing. (FH) Head of Testing Department Security/Safety Testing

Erwin Heimbuchner **Operating Testing Officer** Security/Safety Testing



Basis

EN 12209:2016

Test standard: EN 12209:2016

Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Instructions for use

This test report demonstrates serves to the requirements for locks according to EN 12209:2016

Validity

The data and results given relate solely to the tested/described specimen. The classification will be valid as long as the product remains unchanged and the above bases have not changed. The result can be extrapolated in accordance with the specifications given in the product standard under the manufacturer's responsibility. This test/evaluation does not allow any statement to be made on further characteristics of the present structure regarding performance and quality, in particular the effects of weathering and ageing.

Notes on publication

The ift-Guidance Sheet "Advertising with ift test documents' applies.

The cover sheet cannot be used as an abstract.

The report contains a total of 39 pages

