

UKCA Certificate of Constancy of Performance

This is to certify that:

ISEO Serrature SpA
Via San Girolamo, 13
Pisogne
Brescia
25055
Italy

Holds Certificate Number:

0086 CPR 747917

In respect of:

**BS EN 1125:2008 – Mod. MULTIBLINDO EMOTION – MULTIBLINDO EMOTION LATERALE
MULTIBLINDO EMOTION EXIT Panic Exit Devices.
Mechanically operated by either a horizontal push-bar or a horizontal touch-bar, specifically designed
for use in a panic situation on escape routes.**

In compliance with the Regulation (UK) Statutory Instrument 2019 No 465 of the United Kingdom Parliament (Construction Products (Amendment etc.) (EU Exit) Regulations or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product. This certificate was first issued on the date below and will remain valid as long as neither the designated standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the approved product certification body.

For and on behalf of BSI, an Approved
Body for the above Regulation
(Approved Body Number 0086):



Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2021-07-19

Effective Date: 2021-07-19

Latest Issue: 2021-07-19

Page: 1 of 4

...making excellence a habit.™

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747917

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 1: Requirements for panic exit devices in line with BS EN 1125:2008 (to be read in conjunction with Tables 2)		
Product:	Panic exit devices operated by a horizontal bar as covered by the scope of BS EN 1125:2008.	
Intended use:	For doors on escape routes.	
Essential characteristics	Clauses within BS EN 1125:2008	Compliance
		Mod. MULTIBLINDO EMOTION – MULTIBLINDO EMOTION LATERALE MULTIBLINDO EMOTION EXIT
Ability to release (for doors on escape routes)	4.2.1	Pass
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Pass
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	Pass
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	Pass
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Pass
Control of Dangerous substances	4.1.25	Pass
Note:	<i>This details only those essential characteristics as required in the ZA Annex of BS EN 1125:2008 and applicable to a horizontal bar operation.</i>	

First Issued: 2021-07-19

Effective Date: 2021-07-19

Latest Issue: 2021-07-19

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747917

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 2: Product Information – Panic Exit Devices suitable for use on fire and smoke door assemblies.			
No	Description	Additional Information	Model
1	Panic exit device	Panic exit device operated by a horizontal bar	Mod. MULTIBLINDO EMOTION – MULTIBLINDO EMOTION LATERALE MULTIBLINDO EMOTION EXIT
Models		94A0000**69* + 9459** + (7A3*****.A), 94A0000**69* + 9459*** + (7A1*****.A), 94A0000**66* + 9459** (7A34*****.A), 94A0000**66* + 9459** + (7AR6*****.A), 94A0000**66* + 9459** + (7AR7*****.A)	
Lock striking plates		0332*	
Locking point striking plates		033165, 033167, 033169, 033171	
Accessories		94100160 Electric Trim Set ARIES 00E1***10**	
Note		<i>Panic exit devices detailed in table 2 have conformed to the requirements of BS EN 1125:2008, Table 1: Performance characteristics and compliance criteria.</i>	

First Issued: 2021-07-19

Effective Date: 2021-07-19

Latest Issue: 2021-07-19

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747917

Manufacturing Plant	Certified Activities
E01	BS EN 1125:2008 – Building hardware – Panic exit devices operated by horizontal bar, for use on escape routes.



First Issued: 2021-07-19
Latest Issue: 2021-07-19

Effective Date: 2021-07-19