CERTIFICATE OF COMPLIANCE

| Certificate Number | 20 |
|--------------------|----|
| Report Reference | R3 |
| Issue Date | 20 |

20170612-R38166 R38166-20150202 2017-JUNE-12

Issued to: ATHMER OHG SOPHIENHAMMER 59757 ARNSBERG-MÜSCHEDE GERMANY

This is to certify that representative samples of

GASKETING AND EDGE-SEALING MATERIALS FOR FIRE DOORS, POSITIVE-PRESSURE TESTED; GASKETING MATERIALS FOR FIRE DOORS CERTIFIED FOR CANADA

See next page for models

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:

Additional Information:

UL 10C, Positive Pressure Fire Tests of Door Assemblies CAN/ULC S104,Standard Method For Fire Tests Of Door Assemblies See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.

Sa Mell North American Certification Program Bruce Mahrenholz Direct

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20170612-R38166 R38166-20150202 2017-JUNE-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Door threshold seals for fire doors, Models:

Schall-Ex XL-15/30 WS Schall-Ex XL-15/30 OS Schall-Ex L-15/30 WS Schall-Ex L-15/30 OS Schall-Ex Duo L-15 WS Schall-Ex Duo L-15/30 VS Schall-Ex Duo L-15/31 OS Schall-Ex Duo L-15/28 OS Schall-Ex Duo L-15 QFS Schall-Ex Duo L-15 QF Doppeldicht M12/35 double -sided Doppeldicht M12/35 single -sided Stadi L-24/20 WS Stadi L-24/20 OS, Stadi L-24/20 TS Schall-Ex Ultra WS (double-sided) Schall-Ex Ultra OS (double-sided) Schall-Ex Ultra WS (single-sided) Schall-Ex Ultra OS (single-sided) Schall-Ex Applic A (anod.silver) Schall-Ex Applic A (white) Schall-Ex Applic A (oak raw) Schall-Ex L15-FS **NOR810** Schall-Ex L-14/35 EK



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

