SKG-IKOB PRODUCTCERTIFICATE 428.312.05

Date of issue: 30-08-2017





Certificate holder

Iseo Serrature SpA Via San Girolamo 13 I-25055 Pisogne

T: +39 0364 8821

E: iseo@iseo.com I: www.iseo.com

Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder

delivered under logo / brand:

ISEO / sapa

delivered under type- and / or article number:

F6 Extra / F99 - SKG dubbel; F6 Extra / F99 - SKG enkel

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Iseo Serrature SpA
Number: 428.312.05
page 2 of 2

1. PRODUCT TYPE

euro profile cylinder cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation

Construction: double or single

System: vertical key profile; 1 row of 6 mechanical operated detainers w/wo 2 tot 5 side detainers

Material: cylinder body: brass with various coatings

Dimension: 17 mm profile from 30 mm in various extensions per 5 mm

Fixing: 1 steel bolt M5, length ≥ backset + 10 mm

Intended use: in combination with cylinder mortice locks and security furniture

3. DELIVERY

The delivery includes an installation instruction:

KW13390

4. PERFORMANCES

A euro profile cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with
respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are
fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

• the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).