Evidence of Performance

Joint sound reduction of seals

Test Report N° 17-003502-PR01

(PB Z04-K06-04-en-01)

Client Athmer OHG Sophienhammer 59757 Arnsberg

Germany

Lowerable floor seal, single-side activation

Stadi L-17/20 WS Designation

Cross section of 20 mm x 17 mm sealing groove

varying, 5 mm, 7 mm, 10 mm, 12 mm and 16 mm

Special features none

> Weighted sound reduction index of joints R_{s,w,0} Spectrum adaptation terms C and Ctr



 $R_{S,w,\theta}(C; C_{tr}) = 52 (-1; 0)dB$

Nominal weighted sound reduction index for floor seals with air gap w = 7 mm

ift Rosenheim 03.08.2020

Dr. Joachim Hessinger, Dipl.-Phys. Head of Testing Department **Building Acoustics**

Florian Brechleiter, MSc, Dipl.-Ing. (FH) Operating Testing Officer **Building Acoustics**



Basis

EN ISO 10140-1: 2016 EN ISO 10140-2: 2010 EN ISO 717-1: 2013

Test report 17-003502-PR01 (PB Z04-K06-04-de-01) dated 14.02.2018

Representation



Instructions for use

the comparison of construction products designed for sealing (e.g. gaskets/seals, fillers for joints). The results can be used to evaluate the sound power ratio τ_e according to EN 12354-3 Annex B. Using the calculated sound reduction of the joint for the calculation of the overall sound reduction is not a substitute for the sound reduction verification of the overall construction. For Germany the following applies:

This procedure is suitable for

The weighted joint sound reduction index R_{s,w} can be used for the prognosis of the sound insulation of doors according to DIN 4109-35:2016.

Validity

The data and results given relate solely to the tested and described specimen. Testing the sound insulation does not allow any statement to be made on any further characteristics of the present construction regarding performance and quality.

Notes on publication

The ift Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

The cover sheet can be used as abstract.

Contents

The test report contains a total of 11 pages.

- Object
- Procedure
- Detailed results
- Instructions for use Data sheet (1 page)



